

TamlynWrap® ProSelect Self Adhered

Tech Support / Sales: 800-334-1676
www.tamlyn.com



DESIGN FEATURES

TamlynWrap® ProSelect SA is an innovative product from Tamlyn that combines a high performance Water Resistive Barrier (WRB) with a continuous adhesive backing. Installation achieves ideal vapor permeability while providing robust moisture and air infiltration protection with no requirement for special equipment or tools.

SUPERIOR WATER AND AIR TIGHTNESS

TamlynWrap® ProSelect SA bridges gaps in sheathing and seals along overlaps for a continuous barrier layer that easily integrates with other wall components. This contributes to better overall moisture protection and energy efficiency.

NO FASTENERS REQUIRED

TamlynWrap® ProSelect SA has an advanced full coverage acrylic adhesive for a durable water and air tight installation. The product does not require seam tape and is self-sealing around cladding fasteners.

VAPOR PERMEABLE (>20 Perms When Installed)

The adhesive and substrate layers are vapor permeable which facilitates the effective drying of wall components and mitigates potential moisture accumulation as well as the damaging effects of mold and rot.

MEETS CODE REQUIREMENTS

Meets or exceeds the ICC acceptance criteria requirements for water resistive barriers (AC38) and adhesion (AAMA 711). Code approval per ICC ESR-3670

BEST PRACTICE

TamlynWrap® ProSelect SA must be installed SHINGLE FASHION and integrated with other wall components to promote positive mechanical drainage. All horizontal and vertical overlaps shall be 4" with a 6" overlap at any corners. For full adhesion, product must be rolled in place with a hard roller. May be installed when substrate temperatures are >25F° without a primer provided surfaces are clean and free of debris or contaminants. Primer may be required for porous or challenging surfaces.

When your building envelope requires a quality layer of protection with added airtightness and no fasteners required, TamlynWrap® ProSelect SA is the right choice for the professional builder, designer or contractor. TamlynWrap® ProSelect SA is a high-performance water and air resistive barrier with a full coverage, vapor permeable, advanced acrylic adhesive layer. The adhesive is compatible with all common construction materials and may be used in all climate zones. TamlynWrap® ProSelect SA is made from multiple non-woven and barrier layers that provide superior durability and moisture protection with the added air tightness inherent to an adhered installation. Product may be installed when substrate temperatures are >25F° without a primer. The tough non-woven structure is backed by an industry leading warranty of up to 25 years making TamlynWrap® ProSelect SA the right choice for your residential, multi-family or commercial project. TamlynWrap® ProSelect SA is unique in its development for focusing on improving building performance as well as the installation quality and jobsite safety.